



CONICAL HORN ANTENNA KP-640.700 6.1-7.4 GHZ, 20 DBI, LHCP + RHCP CIRCULAR POLARIZATION, 2xN-FEMALE, 50 OHM

KP-640.700 conical horn antenna for 6.1-7.4 GHz WiMAX links: >20 dBi gain, RHCP+LHCP circular polarization, 15°x15° beam, 2x N-Female, 50 Ohm, VSWR <1.5, 150W CW/200W peak power outdoor.

Parameter	Value
Model	KP-640.700
Frequency range	6.1-7.4 GHz
Polarization type	RHCP and LHCP (circular)
Gain	> 20 dBi
Beamwidth	< 15°
Ellipticity coefficient	< 2 dB
F/B ratio	> 43 dB
VSWR	< 1.5
Connector type	N-Type (Female) (optional: SMA-Type (Female))
Weight	0.75 kg

Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that the view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details the customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each of our customers has a 1.5 year warranty and 7 year aftersales support for the whole range of our products.