



**DIRECTED ANTENNA 0.9 M MULTI RANGE 2-15.5 GHZ CIRCULAR
POLARIZATION WITH FEED HORN. MODEL: DRA-09MR2-15CP**



Directed antenna 0.9 m with ultra-wideband 2-15.5 GHz operation, circular polarization, parabolic reflector, interchangeable feed horns for RF monitoring and SATCOM

General Parameters	
Reflector Diameter	Not less than 0.9 m
Operating Frequency Range	2-15.5 GHz
Antenna Type	Single- or dual-reflector parabolic antenna (depending on installation)
Electrical Characteristics	

Gain Values	
15.5	40
15	39,7,0
14	39,3
12	38,0
10	36,4
8	34,5
7	33,3
6	31,9
3	26,0
2	22,4
First Sidelobe Level	Not higher than –14.5 dB relative to main lobe
Polarization	
Polarization Types	Circular (RHCP, LHCP); Linear
Feed System	
Feed Horns	6 interchangeable feed horns depending on operating frequency band

Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that the view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details the customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each of our customers has a 1.5 year warranty and 7 year aftersales support for the whole range of our products.