



DIRECTIONAL ANTENNA 1710-1880 MHZ, 16.9 DB, VERTICAL POLARIZATION, 20 W, GSM1800

Directional GSM1800 monitoring antenna for 1710-1880 MHz with 16.9 dB minimum gain, vertical polarization, -25 dB first side lobe, VSWR ≤ 1.83 , 20 W power, and N-type connection.

Parameter	Value
Operating Frequency Range	1710-1880 MHz
Minimum Gain	16.9 dB
Gain Non-Uniformity	0.4
Maximum VSWR	1.83
Polarization	Vertical
Beamwidth, Horizontal Plane	9.5°
Beamwidth, Vertical Plane	53°
First Side Lobe Level	-25 dB
Input / Output Power, up to	20 W
Input / Output Connection	N-type

Operating Temperature	-20 to +50 °C
Humidity	100% at 20 °C
Weight	5 kg

Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that the view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details the customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each of our customers has a 1.5 year warranty and 7 year aftersales support for the whole range of our products.