



L-BAND LNA



L-band low-noise amplifier is designed for increasing the sensitivity of the satellite communication and navigation systems receivers.

L-band LNA is low-noise amplifier which is designed for increasing the sensitivity of the satellite communication and navigation systems receivers and is applied for low power signal amplifying without significantly decreasing the signal-to-noise ratio by minimizing additional noise.

The amplifier has 50 Ohm impedance and DC pass (optional).

L-band low-noise amplifier features a compact case which protects it from dust and moisture. It is tiny and reliable.

General parameters	
Frequencies range	950 – 2150 Mhz
Gain	32 dB
Flatnes	±3 dB
Input retun loss	-19 dB
Output return loss	-15 dB
Noise Figure	0.7 dB

Output power, P1dB	+20 dBm
Power Supply	
Input Voltage	+7.5 .. +34 V
Power Consumption	2 W
Environmental:	
Operating temperature	-40 to +50 (-40 to +122)
Storage temperature	-60 to +80 (-76 to +176)
Operating humidity	100%, non-condensing
Mechanical	
Dimensions (W x H x D)*	85 x 38 x 23
Weight*	130 g

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters

listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.