



**OMNI ANTENNA 14000-15000 MHZ, >3 DB, LHCP CIRCULAR  
POLARIZATION, 1×N-TYPE OR SMA-TYPE, 50 OHM, MODEL RSWA-KU3-  
3LH360**

OMNI Antenna 14000-15000 MHz with >3 dB gain, LHCP polarization, 360° coverage, 50 Ohm, N-Type or SMA-Type connector, compact Ku-band omni design.

| Parameter             | Value              |
|-----------------------|--------------------|
| Frequency range       | 14000-15000 MHz    |
| VSWR                  | ≤ 1.8              |
| Gain                  | > 3 dB typ         |
| Axial ratio           | < 0.7 (3 dB)       |
| Polarization          | LHCP               |
| Horizontal Beamwidth  | 360°               |
| Vertical Beamwidth    | < 90°              |
| Input power           | 10 W max.          |
| Nominal impedance     | 50 Ohm             |
| Connector             | N-type or SMA-type |
| Operating temperature | -40°C to +50°C     |
| Storage temperature   | -60°C to +80°C     |
| Dimensions            | Ø45 × 120 mm       |
| Weight                | 0.15 kg            |

Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that the view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details the customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each of our customers has a 1.5 year warranty and 7 year aftersales support for the whole range of our products.