



**OMNI ANTENNA 8000-9000 MHZ, >3 DB, LHCP CIRCULAR POLARIZATION,
1×N-TYPE OR SMA-TYPE, 50 OHM, MODEL RSWA-X1-3LH360**

OMNI Antenna 8000-9000 MHz with >3 dB gain, LHCP polarization, 360° coverage, 50 Ohm, N-Type or SMA-Type connector, compact X-band omni design.

Parameter	Value
Frequency range	8000-9000 MHz
VSWR	≤ 1.8
Gain	> 3 dB typ
Axial ratio	< 0.7 (3 dB)
Polarization	LHCP
Horizontal Beamwidth	360°
Vertical Beamwidth	< 90°
Input power	10 W max.
Nominal impedance	50 Ohm
Connector	N-type or SMA-type
Operating temperature	−40°C to +50°C
Storage temperature	−60°C to +80°C
Dimensions	Ø45 × 120 mm
Weight	0.15 kg

Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that the view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details the customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each of our customers has a 1.5 year warranty and 7 year aftersales support for the whole range of our products.