



S-BAND WI-FI HORN ANTENNA 2.05-2.65 GHZ, 17.0 DB, DUAL LHCP + RHCP CIRCULAR POLARIZATION, 2×N-FEMALE, 50 OHM



Directional S-band Wi-Fi horn antenna 2.05-2.65 GHz with 17.0 dB gain, LHCP + RHCP circular polarization, 28° pattern, VSWR ≤ 1.5, 150 W continuous / 200 W peak, 2×N-Female 50Ω for RF links.

Parameters of S-Band Wi-Fi Horn Antenna 2.05-2.65 GHz + Dual Circular Polarization

Parameter	Value
Operating frequency range	2050-2650 MHz
Directivity (gain), min	17 dB
Impedance	50 Ohm
Connector type	N-Type female
Polarization type	Circular (LHCP + RHCP)
Beamwidth at −3 dB, max	28°
Cross-polarization isolation, min	20 dB
VSWR, not more	1,5

Overall dimensions (L × W × H)	305 × 305 × 600 mm
Weight, max	1,6 kg

Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that the view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details the customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each of our customers has a 1.5 year warranty and 7 year aftersales support for the whole range of our products.