



BUC-K-1-23.55



BUC-K-1-23.55 is block up-converter with fixed output power P1dB 1 W (ALC power: 100 mW) and LO of 23.55 GHz.

Input parameters	
Input frequency range, MHz	950 – 1450
Input impedance, Ohm	50
Input level, max, dBm	-2
Input VSWR, max	1.5
Input interface	N-type, female
ALC range, min, dB	25
ALC threshold level, dBm	-27
Local oscillator	
LO frequency, GHz	23.55
LO phase noise, dBc/Hz :	
@1 kHz	-80
@10 kHz	-85

@100 kHz	-100
LO instability, ppm	± 2
Output parameters	
Output frequency range, GHz	24.5-25.0
Output power @P1dB, W	1
ALC output power, mW	100
Gain, min, dB	47
IMD3 level at ALC output, dBc power, max	-37
Output interface	waveguide WR34, flange PBR260
Output VSWR, max	2
Frequency response	
Flatness over Full Band, dB	± 1.5
Spurious	
In-band P1dB, max, dBc	-55
Out-Band, max, dBm	-30
LO leakage at ALC output, dBm power, max	-40
Image rejection, min, dB	60
Power supply	
Input voltage, VDC	18-30 (nominal 24)
Power consumption, max, W	20
Environmental	

Operating temperature, °C	-40 ... +50
Storage temperature, °C	-60 ... +80
Operating humidity, %	100 (non-condensing)
Mechanical	
Dimensions (W x H x D), mm	121×130×79
Weight, kg	1.51

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters

listed on each device webpage.

Note! *All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.*