




## LNB PLL LO 5.75



C-band LNB PLL LO 5.75 is Low Noise Block Down Converter with single LO 5.75 GHz and single 75 Ohm F-type output. LO instability (depends on temp.):  $\pm 2...100$  kHz, Gain: 58 dB, Noise figure: 30K, Output power P1dB: +3 dBm

Input parameters	
Input Frequency	4.5 ... 4.5 GHz
Waveguide interface	WR-229
Flange	CPR-229G
Input VSWR	2.5:1
Impedance	50 Ohm
Output parameters	
Output Frequency	950 ... 1250 MHz
Output VSWR	2.2:1
Output Interface	F-type (female)
Impedance	75 Ohm
Local frequency	

LO frequency	5.75 GHz
LO instability	$\pm 2$ to $\pm 50$ kHz (room temp.) $\pm 10$ to $\pm 100$ kHz (over room temp.)
LO Phase noise:	
@1kHz	-65dBc/Hz
@10kHz	-80dBc/Hz
@100kHz	-95dBc/Hz
@1MHz	-110dBc/Hz
<b>Characteristics</b>	
Gain	58 dB
Flatness	$\pm 2$ dB @ full band
Ripple	$\pm 0.75$ dB @ 30 MHz
Variation	$\pm 2$ dB max
Noise figure	30K max
P1dB	+3 dBm
Image rejection	45 dB min
<b>Power Supply</b>	
Input voltage	+12 V ... + 24 V DC
Required current	300 mA max
<b>Environmental</b>	
Operating temperature	-30 to +60

Storage temperature	-40 to +80
Operating humidity	0% – 95% RH
<b>Mechanical</b>	
Dimensions (W x H x D)	98x70x138 mm
Weight	0.645 kg

*Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and*

*parameters listed on each device webpage.*

**Note!** *All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.*