



## VIDEO MIXER / SWITCHER HD V1.0



Digital Video Mixer / Switcher HD v1.0 is a powerful, easy-to-use and cost-effective technical solution for any production requirements. Video Mixer / Switcher HD v1.0 is also suitable for portable and mobile applications. Rich functional capabilities allow to use our device for live broadcast, show, presentation, interviewing as well as for studio production. Great attention was paid to good visibility and intuitive control of Video Mixer / Switcher HD v1.0.

- Dynamic range adjustment for digital and analog audio.
- Input and output audio signals can be selected by the user with nominal levels -6, -12, -18, -24 dBFs (from the OSD menu).
- Any input audio channel can be applied to any video source (for example - one audio channel for 4 switchable video inputs).
- This mode is useful for working with an external analog audio mixer.
- Mix sound synchronously with video with special type of sound transition – V or Y.
- Assign the Multiview to any outputs.
- Overlay the PiP presets and Titles at once.
- Any input can be assign to any or to all outputs as well.
- Quick configuration.
- It is possible to select the speed of video/audio transition.
- Control the mixer directly or remotely.
- Additional connector for reserve +12B (9...15B) power supply.
- Wireless or wired via Ethernet Intercom system for 4 users – optional.
- Wireless "TALLY" – optional.
- Encoder H.265/H264 – optional.
- 4K Multiview (4 windows) – optional.

Video formats	
HD input	1080 × 50i
	1080 × 25p
SD input	576 × 50i
HD output	1080 × 50i
SD output	576 × 50i
Input format conversion	<p>all inputs can be resized from HD signals to SD, HD/p to HD/i in any supported formats of Video Mixer / Switcher HD</p> <p><b>Note!</b> All inputs cannot be resized from SD signals to HD</p>
Connectivity	
Video inputs	
Sources	<p>Total 14 sources:</p> <ul style="list-style-type: none"> <li>· 10 external (8 × HD/SD SDI (or 4 × HD/SD SDI + 4 × CVBS), 1 × HDMI (DVI-D), 1 × HDMI (DVI-D)/Title)</li> <li>· 4 external (2 media players and 2 still pictures)</li> </ul>
Inputs	<p>Total 10:</p> <ul style="list-style-type: none"> <li>· 8 × SDI (BNC)</li> <li>· 2 × HDMI (DVI-D)</li> </ul> <p>(In1-In6, In9, In10: HD/SD SDI (BNC); In7, In8: HDMI (DVI-D))</p>
CVBS	In3-In6 may be CVBS (BNC)
HDMI	2 × HDMI (DVI-D)
Video outputs	

Outputs	<p>Total 6:</p> <ul style="list-style-type: none"> <li>· 4 × SDI: HD/SD (BNC) outputs assignable to Program; Preview; Program Logo Free; Program Logo + Titles Free; Multi-View;</li> <li>· 2 × HDMI (DVI-D):</li> </ul> <p>1 × HDMI (DVI-D) assignable to Multi-View Output; Program; Preview; Program Logo Free; Program Logo + Titles Free;</p> <p>1 × HDMI (DVI-D) Multi-View</p>
<b>Audio</b>	
Inputs	<p>4 channels XLR balanced (works with external audio mixer) and can be setup as 2 Stereo pairs or 4 Mono inputs 10×Embedded audio (2 ch) vis SDI or HDMI</p>
Outputs	<p>2 channels XLR balanced.</p> <p>Output SDI Embedded Audio-One Stereo-Pair (Group and Pair can be selected).</p> <p>HDMI Out Embedded Audio.</p>
Audio level adjustment	<p>Each audio source, including embedded and analog, can be associated with any or several video sources. “Audio follows Video” switching mode. Audio level control of the all inputs and master audio level output via On Screen Display Menu and PC Switcher Utilities.</p>
<b>General</b>	
Signal processing	10-bit, 4:2:2 Digital component
Multi-View Monitoring	Built-in multiview monitoring (1920×1080i resolution); with embedded audio
Frame synchronizer	Built-in frame synchronizer for each input
Audio processing	20 and 24 bit

Effect / Keyers	WIPE, MIX, CUT
T-Bar	1
Chroma Key	2 works like independent source
Titels	1 HDMI titles via PC from Title Manager program
PIP	4
Buit-in Video Player	Dual player (VC3) on SD card, 2 players work like 2 independent sources. Up to 256 Gb SD Card. Clip capacity up to 4 hours of a video content. 1 Player (HD Playout) from PC
Built-in Still-image	2 Still-images can be assigned on 2 independent buttons. Up to 32 slides can be uploaded from SD card (Slide 1/2), it works like 2 independent sources. Also technological slides can be assigned instead of the each inputs: technological slides upload on In1-In8 from PC and on In9-In10 from SD card
Built-in Logo insertions and Clock	8 Logos (1 Logo is dinamic) and 1 Clock, up to 8 Logos can be uploaded from PC in the Video Mixer/Switcher memory and then asigned on independent buttons "Logo 1" and "Logo 2". Clock can be switched on/off with independent button. Location of Logos and Clock can be set up from PC
Internal Frame Memory	Up to 256 Gb SD card. Clip capacity up to 4 hours of a video content
Pattern Generator	Color BARS and audio signal source (1kHz, 0dB), Black
PC control	Simultaneous operation from console and PC
Options	H.265 encoder, camera channel unit, intercom

Interfaces	
Ethernet 100 (1×RJ-45)	F/W ugrade; Upload Still Image; Logo Insert; Keyboard Controller
Tally Output	D-Sub 15 pin (F)
RS-232	1 × RS-232 on 9-pin D-sub female controls and power supply for Keyboard Controller up to 20 m
Power Supply	
Consumption	+12 V, 7A (consumption of video mixer 2.75A)
Size and Weight	
Main Unit	440×220×88mm (2U), ~3.9kg
Control Panel	440×220×44mm, ~2.4kg

*Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.*

**Note!** All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.