



ULTRA-WIDEBAND BICONICAL OMNIDIRECTIONAL ANTENNA 0.3-8.0 GHZ, 5 DBI, LINEAR VERTICAL POLARIZATION, 1×N-FEMALE, 50 OHM

Passive UWB biconical omnidirectional antenna 0.3-8.0 GHz (300-8000 MHz), 5 dBi, linear vertical polarization, 1×N-Female, 50Ω, VSWR ~1.1-1.6, RF mast mount, Ø310×200 mm, 2.5 kg.

Characteristic	Value
Type	Omnidirectional
Operating frequency range	0.3-8.0 GHz
Application	Outdoor
Gain	5 dBi
Polarization type	Vertical, linear
VSWR, max	1.6
Diameter	310 mm
Length	200 mm
Mounting type	Mast mount
Impedance	50 Ohm

Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that the view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details the customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each of our customers has a 1.5 year warranty and 7 year aftersales support for the whole range of our products.